

LED Programmable Vehicle Identification Displays



Bright & Rugged LED Displays ▪ **Most Dependable in the Industry** ▪ **Maintenance Free** ▪ **Field Tested for Over 17 Years!**



12", VID-3N12L-G shown above

NVIZN™ LED Programmable Displays are the most efficient form of LED displays Driver Industrial Safety™ has to offer. Recognized globally for dependability, high visibility, and programmable functionality. LED Programmable displays provide the most robust and efficient solution to identify any vehicle or heavy equipment especially under extreme, low visibility weather conditions. NVIZN™ products have proven to be the most visible enabling continuous Day and Night operation on countless mine sites with the luxury of no maintenance. We offer up to (5) characters within our Single-Framed displays for users to efficiently program multiple numbers, letters, or characters and/or messages for required equipment identification. Determine your Mounting and Distance Criteria™ (DC) requirements to ensure you select the right Type, Size or a Combination of displays to safeguard workers and site management so they are easily able to identify unit number, unit status, speed limit, payload weight, or otherwise, from afar. Count on Driver Industrial Safety™ to protect your valued Personnel & Assets!

IP RATED
IP66/IP67

Available in
120-240/277
VAC

Lightweight &
Easy to Install!



9 inch Numeric Displays, Programmable 0 to 9


Part Number		LED Color	3 Digit, LED Programmable				Voltage from 10 to 30 VDC!			
VID-3N9-R	VID-3N9-A	Red	Digits	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-3N9-G	VID-3N9-B	Green Blue	3	228.6 mm 9 in	4.9 kg 11 lbs	346.7 mm 13.65 in	438.15 mm 17.25 in	24	0.50	12
Accessories:		Mounting Brackets VID-S9-2	Power Extension Cord VID-PC-EXT-50-1	Power Cord Splitter 2 VID's VID-PC-EXT9-2Y	Power Cord Splitter 3 VID's VID-PC-EXT9-3Y					

**VISIBLE UP TO
2000ft/610m!**

Multiple LED Color
Options Available!

12 inch Numeric Displays, Programmable 0 to 9

Part Number		LED Color	2 to 4 Digit, LED Programmable				Voltage from 10 to 30 VDC!			
VID-2N12L-R	VID-2N12L-A	Red	Digits	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-2N12L-G	VID-2N12L-B	Green Blue	2	304 mm 12 in	7 kg 15.5 lbs	438.15 mm 17.25 in	498.10 mm 19.61 in	24	0.33	8
VID-3N12L-R	VID-3N12L-A	Red	Digits	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-3N12L-G	VID-3N12L-B	Green Blue	3	304 mm 12 in	9.3 kg 20.5 lbs	438.15 mm 17.25 in	710.95 mm 28.02 in	24	0.49	12
VID-4N12L-R	VID-4N12L-A	Red	Digits	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-4N12L-G	VID-4N12L-B	Green Blue	4	304 mm 12 in	11.2 kg 24.8 lbs	438.15 mm 17.25 in	923.80 mm 36.37 in	24	0.66	16
Accessories:		Mounting Brackets VID-S12-2	Power Extension Cord VID-PC-EXT-50-1	Power Cord Splitter 2 VID's VID-PC-EXT12-2Y	Power Cord Splitter 3 VID's VID-PC-EXT12-3Y					



12 inch Character Displays, Programmable A to Z and 0 to 9

Part Number		LED Color	2 to 5 Character, LED Programmable				Voltage from 10 to 30 VDC!			
VID-2C12-24V-R	VID-2C12-24V-A	Red	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-2C12-24V-G	VID-2C12-24V-B	Green Blue	2	304 mm 12 in	10.4 kg 23 lbs	438.15 mm 17.25 in	622.05 mm 24.49 in	24	1.00	24
VID-3C12-24V-R	VID-3C12-24V-A	Red	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-3C12-24V-G	VID-3C12-24V-B	Green Blue	3	304 mm 12 in	11.6 kg 25.5 lbs	438.15 mm 17.25 in	895.35 mm 35.25 in	24	1.50	36
VID-4C12-24V-R	VID-4C12-24V-A	Red	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-4C12-24V-G	VID-4C12-24V-B	Green Blue	4	304 mm 12 in	14.1 kg 31 lbs	438.15 mm 17.25 in	1171.95 mm 46.05 in	24	2.00	48
VID-5C12-24V-R	VID-5C12-24V-A	Red	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-5C12-24V-G	VID-5C12-24V-B	Green Blue	5	304 mm 12 in	18.59 kg 41 lbs	438.15 mm 17.25 in	1443.99 mm 56.85 in	24	2.50	60
Accessories:		Mounting Brackets VID-S12-2	Power Extension Cord VID-PC-EXT-50-1	Power Cord Splitter 2 VID's VID-PC-EXT12-2Y	Power Cord Splitter 3 VID's VID-PC-EXT12-3Y					

18 inch Character Displays, Programmable A to Z and 0 to 9

18" Character - Visible up to 1000ft / 300m

Part Number	LED Color	1 Character, LED Programmable					Voltage from 10 to 30 VDC!		
Character	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts		
VID-1C18-24V-R	Red	1	457.2 mm 18 in	7.3 kg 16 lbs	575.31 mm 22.65 in	438.15 mm 17.25 in	24	1.00	24
VID-1C18-24V-A	Amber								
VID-1C18-24V-G	Green								
VID-1C18-24V-B	Blue								
Accessories:		Mounting Brackets VID-S18-2	Power Extension Cord VID-PC-EXT-50-1	Power Cord Splitter 2 VID's VID-PC-EXT18/24-2Y		Power Cord Splitter 3 VID's VID-PC-EXT18/24-3Y			

24 inch Character Displays, Programmable A to Z and 0 to 9

24" Character - Visible up to 1500ft / 457m


Part Number	LED Color	1 Character, LED Programmable					Voltage from 10 to 30 VDC!		
Character	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts		
VID-1C24-24V-R	Red	1	609.6 mm 24 in	9.5 kg 21 lbs	803.91 mm 31.65 in	438.15 mm 17.25 in	24	1.50	36
VID-1C24-24V-A	Amber								
VID-1C24-24V-G	Green								
VID-1C24-24V-B	Blue								
Accessories:		Mounting Brackets VID-S24-2	Power Extension Cord VID-PC-EXT-50-1	Power Cord Splitter 2 VID's VID-PC-EXT18/24-2Y		Power Cord Splitter 3 VID's VID-PC-EXT18/24-3Y			

36 inch Character Displays, Programmable A to Z and 0 to 9


36" Character - Visible up to 2000ft / 610m

Part Number	LED Color	1 Character, LED Programmable					Voltage from 10 to 30 VDC!		
Character	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts		
VID-1C36-24V-R	Red	1	914.4 mm 36 in	12.2 kg 27 lbs	1032.51 mm 40.65 in	438.15 mm 17.25 in	24	2.50	60
VID-1C36-24V-A	Amber								
VID-1C36-24V-G	Green								
VID-1C36-24V-B	Blue								
Accessories:		Mounting Brackets VID-S36-2	Power Extension Cord VID-PC-EXT-50-1	Power Cord Splitter 2 VID's VID-PC-EXT36-2Y		Power Cord Splitter 3 VID's VID-PC-EXT36-3Y			


VISIBLE UP TO 2000ft/610m!



VID-1C18-24V-G



VID-1C24-24V-A



VID-1C36-24V-B

For Display Accessories (refer to pg 8)

A B W G R Multiple LED Color Options Available!

LED Message Board Displays: Dynamic Communication Capability

VISIBLE UP TO 500ft/152m!

IP RATED
IP66/IP67

5 YEAR LIMITED WARRANTY

Identifies Equipment that is down or needs assistance

A B G R : Multiple LED Color Options Available!

VID-3C12-MBCA-A (without remote)
VID-3C12-MBCA-A-KIT (with remote) shown below

(Also Sold Separately)
VID-M3XCR



Up to 3 Characters - 17.25"H (438.15mm) x 35.25"L (895.35mm) | 12V to 24V | 25.5lbs (11.6kg) | 36 Watts

** Must Purchase Communication Cable (VID-PC-COMM-60) per Display to link to unit **

Driver Industrial Safety's Message Board Displays supercede expectations of Smart Communication! Armed with advanced communication capabilities, this NVIZN™ product instinctively enables the built-in Smart Communication providing a seamless connection from the display to your intelligent software, device, or vehicle as needed. Many sites have the need to convey displaying the payload to the shovel operator as the truck is being loaded, vehicle speed limit, low battery alert, truck wash bay traffic signals and direction, and much more. These communication ideas our LED Message Boards relay are utilized on many industrial and commercial sites. Messages are pre-programmed to display ones Equipment Status, Arrows for Traffic Guidance along with various other communication requirement needs.

- ▶ Custom Programming
- ▶ Sealed System Display for Protection
- ▶ Real-Time Programming Capability
- ▶ External Waterproof Pigtail
- ▶ Message Vehicle Number Lock
- ▶ Easy Touch-Screen Controls
- ▶ LED Viewing Screen



VID-PYLD-R
with remote
(VID-PYLD-Communication Module)

NEW! PAYLOAD DISPLAY
Assists both Digger & Loader Operators! Displays are mounted to the Haul Truck, in view of operator, displaying "Real Time" Payload weights as materials are being loaded onto a Dump Truck.

Additional Features:
Displays Vehicle's Speedometer, Truck #, and Flashes when Truck is Overloaded!

LED Signal Light Displays: Advanced LED Backlit Technology

VISIBLE UP TO 2000ft/610m!

IP RATED
IP66/IP67

5 YEAR LIMITED WARRANTY

Identifies Equipment that is down or needs assistance

A B W G R : 2 or 3 Color Combinations Available!



Multiple Colors Available!
(2 or 3 color)

VID-BL2SIG6-24V-R/B-KIT (with remote) shown above

BL2SIG6-24V-R/B (without remote)

Lit Up!



These displays are operational as a Signaling device to indicate a mode of operation of a vehicle, a direction of a vehicle, type of use of equipment, signal needs to others, a directional help on a site, or a vehicle is in use at that time. Driver Industrial Safety's NVIZN™ Signal Light displays use coloration such as "Red Light, Green Light" signaling to indicate use or directional flow of equipment, personnel or vehicle surrounding it when in use or indicate the function of vehicle needed for signaling others on site. Signal Lights provide color signaling uses which denotes what use it is being used at, such example as forward and reverse; or an autonomous mode or manual driver indicator, or to denote traffic direction such as stop or go, pass or do not pass by to bystanders alongside the vehicle(s) or intersections; etc.

- ▶ Available in 110V & 220V upon request (refer to factory for wire hireness)
- ▶ Operating Temperatures ranging from 50°C (-58°F) to +60°C (140°F)
- ▶ Dimensions: 11"H (279.40mm) x 35.37"L (898.40mm)
- ▶ 12V (1.20Amps) to 24V (.60Amps) | 15lbs (6.80kg) | 14.40 Watts

LED Reflective Backlit Vehicle Identification Displays



Bright & Rugged LED Displays ▪ **Most Dependable in the Industry** ▪ **Maintenance Free** ▪ **Field Tested for Over 17 Years!**

LED Reflective Backlit Displays are a solid solution for 24hr Equipment Visibility. NVIZN™ Backlit Displays are rugged, super-sealed and engineered with customizable 3M™ Diamond Grade™ reflective Unit Numbers or Message to ensure maximum visibility both day and night whether your vehicle (and display) are powered on or off. Depend on Driver Industrial Safety's NVIZN™ products for reliable equipment management solutions!

DESIGNED FOR 24 HOUR USE!



A Y W R

Multiple Reflective Color Options Available!

9 inch Character Displays, Reflective Backlit A to Z and 0 to 9

IP RATED
IP66/IP67

9" Character - Visible up to 350ft / 107m

12 Volt available upon request

Part Number	Reflective Color	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-BL3N9-24V-BKA	Amber	2 to 4	228.8 mm 9 in	4.90 kg 11 lbs	346.70 mm 13.65 in	438.15 mm 17.25 in	24	0.50	12
VID-BL3N9-24V-BKY	Yellow Green								
VID-BL3N9-24V-BKW	White								
VID-BL3N9-24V-BKR	Red								

Accessories: Mounting Brackets (VID-S9-2), Power Extension Cord (VID-PC-EXT-50-1), Power Cord Splitter 2 VID's (VID-PC-EXT9-2Y), Power Cord Splitter 3 VID's (VID-PC-EXT9-3Y)

12 inch Character Displays, Reflective Backlit A to Z and 0 to 9

12" Character - Visible up to 500ft / 152m

12 Volt available upon request

Part Number	Reflective Color	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-BL3N12-24V-BKA	Amber	2 to 4	304.0 mm 12 in	11.34 kg 25 lbs	438.15 mm 17.25 in	654.05 mm 25.75 in	24	3.75	90
VID-BL3N12-24V-BKY	Yellow Green								
VID-BL3N12-24V-BKW	White								
VID-BL3N12-24V-BKR	Red								

Accessories: Mounting Brackets (VID-S12-2), Power Extension Cord (VID-PC-EXT-50-1), Power Cord Splitter 2 VID's (VID-PC-EXT12-2Y), Power Cord Splitter 3 VID's (VID-PC-EXT12-3Y)

16 inch Character Displays, Reflective Backlit A to Z and 0 to 9

16" Character - Visible up to 750ft / 230m

12 Volt available upon request

Part Number	Reflective Color	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-BL3C16-24V-BKA	Amber	Up to 4	406.4 mm 16 in	16.33 kg 36 lbs	539.75 mm 21.25 in	895.35 mm 35.25 in	24	5.63	135
VID-BL3C16-24V-BKY	Yellow Green								
VID-BL3C16-24V-BKW	White								
VID-BL3C16-24V-BKR	Red								

Accessories: Mounting Brackets (VID-S12-2), Power Extension Cord (VID-PC-EXT-50-1), Power Cord Splitter 2 VID's (VID-PC-EXT16-2Y), Power Cord Splitter 3 VID's (VID-PC-EXT16-3Y)

18 inch Character Displays, Reflective Backlit A to Z and 0 to 9

18" Character - Visible up to 1000ft / 300m

12 Volt available upon request

Part Number	Reflective Color	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-BL1C18-24V-BKA	Amber	1	457.20 mm 18 in	7.30 kg 16 lbs	575.31 mm 22.65 in	438.15 mm 17.25 in	24	1.00	24
VID-BL1C18-24V-BKY	Yellow Green								
VID-BL1C18-24V-BKW	White								
VID-BL1C18-24V-BKR	Red								

Accessories: Mounting Brackets (VID-S18-2), Power Extension Cord (VID-PC-EXT-50-1), Power Cord Splitter 2 VID's (VID-PC-EXT18-2Y), Power Cord Splitter 3 VID's (VID-PC-EXT18-3Y)

24 inch Character Displays, Reflective Backlit A to Z and 0 to 9

24" Character - Visible up to 1500ft / 457m

12 Volt available upon request

Part Number	Reflective Color	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-BL1C24-24V-BKA	Amber	1	609.60 mm 24 in	9.50 kg 21 lbs	803.91 mm 31.65 in	438.15 mm 17.25 in	24	1.50	36
VID-BL1C24-24V-BKY	Yellow Green								
VID-BL1C24-24V-BKW	White								
VID-BL1C24-24V-BKR	Red								

Accessories: Mounting Brackets (VID-S24-2), Power Extension Cord (VID-PC-EXT-50-1), Power Cord Splitter 2 VID's (VID-PC-EXT24-2Y), Power Cord Splitter 3 VID's (VID-PC-EXT24-3Y)

36 inch Character Displays, Reflective Backlit A to Z and 0 to 9

36" Character - Visible up to 2000ft / 610m

12 Volt available upon request

Part Number	Reflective Color	Characters	Character Height	Weight	Frame Height	Frame Width	Volts	Amps	Watts
VID-BL1C36-24V-BKA	Amber	1	914.40 mm 36 in	12.70 kg 28 lbs	1032.51 mm 40.65 in	438.15 mm 17.25 in	24	4.17	100
VID-BL1C36-24V-BKY	Yellow Green								
VID-BL1C36-24V-BKW	White								
VID-BL1C36-24V-BKR	Red								

Accessories: Mounting Brackets (VID-S36-2), Power Extension Cord (VID-PC-EXT-50-1), Power Cord Splitter 2 VID's (VID-PC-EXT36-2Y), Power Cord Splitter 3 VID's (VID-PC-EXT36-3Y)



VISIBLE UP TO 2000ft/610m! For Display Accessories (refer to pg 8)



NEW! **12" & 16" INTERCHANGEABLE CHARACTER**
LED Reflective Backlit Displays - same build as our standard displays, constructed with the same super-sealed frame!
(For Product Details, refer to pg 8)



Featured NVIZN™ Products: Custom Identification Displays

Bright & Rugged LED Displays ▪ **A Y W R** Various 3M™ Reflective Color Options ▪ Easy to Install & Maintenance Free!

Interchangeable Character Reflective Backlits



VID-BLE3C16-BKY
(with Fluorescent Yellow Green Characters)

16 INCH

Purchase Your Custom Number Kit TODAY!
*Combination Letter Kits Available Upon Request



ALL PARTS ARE INTERCHANGEABLE & EASY TO INSTALL!

- ▶ 2 to 4 Character 16" LED, Reflective Backlit
- ▶ 2 to 4 Positions for Interchangeable Characters
- ▶ Advanced Backlit Technology for Max Visibility
 - ▶ Advanced Temperature Control LEDs - (Shock and Vibration Resistant)
- ▶ 3M™ Diamond Grade™ Reflective Characters

- ▶ Reverse Polarity Protected
- ▶ Built to Survive Extreme Environments
 - ▶ Black Aerospace-Grade Aluminum Frame
 - ▶ Impact Resistance and Sealed Lens
 - ▶ Withstands Power-Hose Cleaning
- ▶ Lightweight and Easy to Install!
- ▶ Available in 110VAC & 220VAC
- ▶ Rated IP66 & IP67
- ▶ Standard Reflective Color Options
 - ▶ Fluorescent Yellow Green (Y)
 - ▶ Fluorescent Amber (A)
 - ▶ Fluorescent White (W)
 - ▶ Fluorescent Red (R)
- ▶ Visible up to 750ft (230m)!

Part Number	Character Height	Weight	Frame Dimensions		Volts (VDC)	Amps	Watts
			Height	Width			
<i>x = reflective color</i>					12	11.25	135
VID-BLE3C16-24V-BKx (2 to 4 characters)	16" 406.40 (mm)	36 LBS 16.33 (kg)	21.25" 539.75 (mm)	35.25" 895.35 (mm)	24	5.63	135

3-Sided LED Reflective Backlits



LIGHT DUTY (For Pick-up Trucks or Passenger Vehicles)




VID-SA
(shown above with LED Beacon)

- ▶ Internal High Performance Illumination with Backlit Technology and 3M™ Diamond Grade™ Reflective material for Day & Night Visibility!
- ▶ Up to (4) Character & Numeric Options
- ▶ High-illumination with standard powered 12VDC Cigarette Cord. **Powered & Non-powered Options!**
- ▶ Heavy Duty Ultra-High Density shell providing resistance towards water and extreme weather!
- ▶ Constructed with (3) Heavy Duty Magnets withstanding speeds of up to 50 MPH (80km/hr)
- ▶ Lightweight & Easy to Install, No Maintenance!



(3) Heavy Duty Magnetic Feet with Cigarette Cord



Also Available with or without a Whip and/or Beacon!

VID-S **UPM3-VSA** (shown with VID-SA)

Part Number	Character Height	Weight	Display Dimensions		Volts (VDC)	Amps	Watts
			Height	Width			
<i>x = reflective color</i>					12	.156	1.87
VID-S (2 to 4 characters)	7.25" 184.15 (mm)	6 LBS 2.72 (kg)	8.00" 203.20 (mm)	20" x 20" x 20" 20" = 508 (mm)	24	.078	1.87

SUPER DUTY (For Auxiliary Equipment Identification)



12"H characters

- ▶ Consists of (3) NVIZN™ displays mounted on a 3-Sided, Super Duty frame structure for clear visibility at multiple angles Day and Night!
- ▶ 3M™ Diamond Grade™ Reflective Characters
- ▶ Advanced Backlit Technology for Max Visibility
 - ▶ Advanced Temperature Control LEDs - (Shock and Vibration Resistant)
- ▶ Open-Framed structure built to survive the most Extreme Environmental Conditions!
 - ▶ Black Aerospace Grade Aluminum Frame
 - ▶ Impact Resistance and Sealed Lens
 - ▶ Withstands Power-Hose Cleaning

- ▶ Reverse Polarity Protected
- ▶ Visible up to 500ft (152m)!



Frame also Compatible with LED Programmable Displays!
LED Color Options: **R** Red **A** Amber **G** Green **B** Blue

Part Number	Character Height	Weight	Overall Frame Dimensions		Volts (VDC)	Amps	Watts
			Height	Width			
<i>x = reflective color</i>					12	22.60	270
VID-3SBL3N12CS-x (Up to 4 characters)	12" 304.80 (mm)	110 LBS 49.90 (kg)	24.61" 625.10 (mm)	32.38" 822.45 (mm)	24	11.30	270

MEDIUM DUTY (For Auxiliary Equipment)


Rubber Tire Dozers & Graders



VID-LA
(shown above with LED Beacon)

- ▶ Manufactured with 3M™ Diamond Grade™ Reflective material for CLEAR Nighttime Visibility when equipment is turned off!
- ▶ Up to (4) Character & Numeric Options
- ▶ High-illumination with standard powered 12VDC Cigarette Cord. **Powered & Non-powered Options!**
- ▶ Heavy Duty Ultra-High Density shell providing resistance towards water and extreme weather!
- ▶ Constructed with (4) Heavy Duty Magnets with up to 600 lbs (272.15kg) of magnetic pull!
- ▶ No Maintenance & Easy to Install!

Also Available with or without a Whip and/or Beacon!




(4) Heavy Duty Magnetic Feet with Cigarette Cord



Part Number	Character Height	Weight	Display Dimensions		Volts (VDC)	Amps	Watts
			Height	Width			
<i>x = reflective color</i>					12	.156	1.87
VID-L (2 to 4 characters)	8.30" 210.82 (mm)	20 LBS 9.07 (kg)	10.00" 254 (mm)	28" x 28" x 28" 28" = 711 (mm)	24	.078	1.87

NVIZN™ Display Accessories



Mounting Brackets, Communication Cables, Power Supply & Converters, Power Cords, Power Harnesses, and much more!

We supply high quality Mounting Hardware and Communication Accessories for your NVIZN™ Identification Display. Multiple sizes, lengths and customizable options are readily available to maximize the performance of your display. Purchase yours today!



VID-S12-2
Steel Mounting Bracket Set (includes Hardware)



VID-110-240V PS
Power Supply, 2 Pin Male Deutsch (277 Vac to 24Vdc)



VID-PC12-50-1
50 ft Power Cord Extension, 12 gauge, 2-Wire with Deutsch Connector



VID-PC14-25-2
25 ft Power Cord Extension, 14 gauge, with Deutsch Connector on both ends



VID-PC16-50-1
50 ft Power Cord Extension, 16 Gauge, 2-Wire with Deutsch Connector